



CULTURE OF SOUND



# KR SERIES CATALOGUE

LATEST EDITION



# KR Series

## PASSIVE CABINETS FOR CLUBS & KTV

The two full-range models belonging to the KR Series have been specifically designed for installations where high volume is required whilst delivering excellent vocal clarity with low distortion. They are available in two-way passive 10" and 12" versions.

Ideal for a wide range of fixed installation applications, such as KTV rooms, conference halls, houses of worship or multimedia spaces.

The double port located at the rear of the enclosure creates increased bass frequency response. When installed close to a wall, it creates a reflection that extends the low frequency response of the system, creating extra bass boost.

- ✔ KTV rooms
- ✔ Clubs & bars
- ✔ Public buildings
- ✔ Sound reinforcement
- ✔ Houses of worship
- ✔ Multi media spaces
- ✔ Conference halls

## KR-12



The KR-12 is a compact, two-way passive cabinet. Consists of a 12" (3" voice coil) LF transducer with total waterproof cone treatment. The 1" HF compression driver delivers excellent sonic quality. It has an exceptional dynamic range and produces even the most complex signals with depth and definition and is mounted on a 90° x 60° rotatable horn.

<b>Components</b>	LF: 12" speaker, 3" (75 mm) copper wire voice coil, waterproof cone with treatment on both sides HF: 1" exit throat (38 mm) voice coil, BMS annular diaphragm driver
<b>Max SPL</b>	124 dB / 130 dB Peak
<b>Coverage</b>	90° x 60° rotatable
<b>Rated power</b>	500 W AES (1000 W program, 2000 W Peak)
<b>Dimensions</b>	600 x 363 x 410 mm (H x W x D)
<b>Weight</b>	24 Kg (52.9 lbs)
<b>Fittings</b>	14 x M8, ergonomic handle on the back position, 4 x M6 U-bracket, 4 x M6 wall bracket, 35 mm top hat

## KR-10




The KR-10 is a compact, two-way passive cabinet. Consists of a 10" (2.5" voice coil) LF transducer with waterproof cone. The 1" HF compression driver delivers excellent sonic quality. It has an exceptional dynamic range and produces even the most complex signals with depth and definition and is mounted on a 90° x 60° rotatable horn.

<b>Components</b>	LF: 10" speaker, 2.5" (50 mm) fiber glass former and aluminium winding voice coil, waterproof cone with treatment on both sides HF: 1" exit throat (38 mm) voice coil, BMS annular diaphragm driver
<b>Max SPL</b>	122 dB / 128 dB Peak
<b>Coverage</b>	90° x 60° rotatable
<b>Rated power</b>	300 W AES (600 W program, 1200 W Peak)
<b>Dimensions</b>	550 x 295 x 330 mm (H x W x D)
<b>Weight</b>	16 Kg (35.2 lbs)
<b>Fittings</b>	14 x M8, ergonomic handle on the back position, 4 x M6 U-bracket, 6 x M6 wall bracket, 35 mm top hat

## ACCESSORIES **KR** SERIES

**KR-10**


**AGR-8**  
Eye bolt



**WB-20/3**  
Wall bracket



**UBR-KR10**  
U bracket



**KR-12**


**AGR-8**  
Eye bolt



**WB-20/3**  
Wall bracket



**UBR-KR12**  
U bracket





# LYNX

pro-audio

CULTURE OF SOUND



[www.lynxproaudio.com](http://www.lynxproaudio.com)