

Key features

- Compact & versatile
- Powered from the sub unit
- DSP presets for wide applications
- Weather proof components
- Easy to use, easy to install
- Portable
- Available in black or white

Applications

- PA system
- Clubs & Theatres
- Houses of worship
- Solo artists, band, DJ
- Public buildings
- Commercial complex

General description & specs

The ionic-50 is a passive column speaker part of the ionic series. The ionic cabinets are compact, modular and powerful and the complete serie include two sub units and two column models.

The ionic-50 uses 6 x 3" (0.75" voice coil) neodymium transducers offering a coverage of 15° +/-5° V x 100° H and 119dB SPL.

Weight has been left as low as possible providing easy set ups in fixed installation as well as easy transport for portable applications.

The ionic-50 is powered from the sub bass units which include a Digital Signal Processor offering different presets to cover a wide range of sound applications.



Accessories



SV-12S
Sub adaptor



WB-I
Wall bracket



SV-2I
Cab connection



SV-IONIC
Cab connection

| | | | |
|---------------------------|--------------------------------------|---------------------------|----------------------------------|
| Components | 6 x 3" speaker with 0.75" voice coil | Rated power (AES) | 150 W, 300 W program, 600 W peak |
| | | Nominal Impedance | 32 Ohms |
| Frequency Range | 150 Hz – 20 KHz (-10dB) | Connectors | 2 x Neutrik Speakon NL4MP |
| Frequency Response | 180 Hz - 20 KHz (± 3dB) | Finish | Epoxy paint / bespoke pattern |
| Sensitivity | 97 dB (1W@1m) | Material | 1.5 mm stainless steel |
| Max. SPL | 119 dB - 125 dB peak | Dimensions | 502 x 89 x 117 mm (H x W x D) |
| Coverage | 15° ± 5° V x 100° H | Weight | 7 Kg (15 lbs) |