

LYNX
pro-audio

CULTURE OF SOUND



ROX SERIES CATALOGUE

LATEST EDITION

RX-8



The RX- 8 is a high-performance polypropylene, 2-way active PA system featuring a 8-inch low-frequency driver. Powered by a Class D amplifier, it delivers 280 W RMS and can reach a peak output of 600 W, making it ideal for sound reinforcement in both indoor and outdoor environments.

Components	LF: 8", 2" voice coil HF: 1", compression driver
Amplification	Class-D/ DSP FIR Filters
BT	Receiver-TWS Stereo Pairing
Control	LCD Display, encoder and push button
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Coverage	90°H x 60°V
Fittings	3mm (2-position) speaker stand socket and 45° angled wedge for stage monitoring
Power	280W RMS / peak 600W
Frequency Response	65 Hz to 20 kHz
SPL Max	118 dB - 124 dB peak
Power Supply	230V ~ / 50Hz mains power supply
Weight	7 Kg (15,43 lbs)
Dimensions	435 x 245 x 295 mm (H x W x D)

RX-10



The RX- 10 is a high-performance polypropylene, 2-way active PA system featuring a 10-inch low-frequency driver. Powered by a Class D amplifier, it delivers 280 W RMS and can reach a peak output of 600 W, making it ideal for sound reinforcement in both indoor and outdoor environments.

Components	LF: 10", 2" voice coil HF: 1", compression driver
Amplification	Class-D/ DSP FIR Filters
BT	Receiver-TWS Stereo Pairing
Control	LCD Display, encoder and push button
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Fittings	35mm (2-position) speaker stand socket and a 45° angled wedge for stage monitoring
Power	280 W RMS / 600 W peak
Frequency Response	45 Hz to 20 kHz
SPL Max	119 dB - 125 dB peak
Coverage	90° H x 60° V
Power Supply	230V ~ / 50Hz mains power supply
Weight	9 Kg (19,84 lbs)
Dimensions	545 x 355 x 295 mm (H x W x D)

RX-12



The ROX-12 is a high-performance polypropylene, 2-way active PA system featuring a 12-inch low-frequency driver. Powered by a Class D amplifier, it delivers 450 W RMS and can reach a peak output of 1000 W, making it ideal for sound reinforcement in both indoor and outdoor environments.

Components	LF: 12", 3" voice coil HF: 1.35", compression driver
Amplification	Class-D
BT	Receiver-TWS Stereo Pairing
Control	LCD Display, encoder and push button
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Fittings	35mm (2-position) speaker stand socket and 45° angled wedge for stage monitoring
Power	450W RMS / peak 1000W
Frequency Response	45Hz to 20 kHz
SPL Max	125 dB - 131 dB Peak
Coverage	90° H x 60° V
Power Supply	230V ~ / 50Hz mains power supply
Weight	19 Kg (41.8 lbs)
Dimensions	609 x 359 x 346 mm (H x W x D)

RX-15



The ROX-15 is a high-performance polypropylene, 2-way active PA system featuring a 15-inch low-frequency driver. Powered by a Class D amplifier, it delivers 450 W RMS and can reach a peak output of 1000 W, making it ideal for sound reinforcement in both indoor and outdoor environments.

Components	LF: 15", 3" voice coil HF: 1.35", compression driver
Amplification	Class- D
BT	Receiver-TWS Stereo Pairing
Control	LCD Display, encoder and push button
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Fittings	35mm (2-position) speaker stand socket and a 45° angled wedge for stage monitoring
Power	450 W RMS / 1000 W peak
Frequency Response	45 Hz to 20 kHz
SPL Max	125 dB 131 dB Peak
Coverage	90° H x 60° V
Power Supply	230V ~ / 50Hz mains power supply
Weight	21 Kg (46.2 lbs)
Dimensions	696 x 417 x 368 mm (H x W x D)



LYNX

pro-audio

CULTURE OF SOUND



www.lynxproaudio.com