

Two-way, full range, passive, 8" loudspeaker with line transformer. Cabinet for background sound reinforcement. It consists of a 8" low/mid woofer with one 1" high frequency dome tweeter. It offers 100° x 90° dispersion, 108 dB SPL and 160 W program.



### Key features

- Ultra-compact, high performance
- Background sound reinforcement
- LUKA processor optimised preset
- White, black colour
- Rugged design
- Low and High impedance selector with 5 taps
- IP66 for outdoor use with accessory terminal cover
- 8 ohm or 100V line operation
- Wall bracket included

### Applications

- Club & Bar installations
- Theatres
- Houses of worship
- Broadcast
- Multi media spaces
- Public address


### General description & specifications

The ELVA-8T is a full range, two way, ultra-compact passive cabinet designed to give exceptional sound quality for distributed applications with high quality background music and speech reproduction.

It features a 8" low/mid transducer with rubber surround and a 1" high frequency driver. Manufactured in high quality ABS a

dedicated wall bracket is included as well as aluminium mesh grill and weatherproof terminal cover with an IP66 rating. The cabinet can be selected as 8ohm low impedance or high impedance for 100V installations via a rotary switch at the rear of the enclosure.

### Dimensional Drawing



### Technical Data

Frequency range	60 Hz – 20 KHz (-10dB)
Frequency response	70 Hz – 18 KHz (± 3dB)
Max SPL @ 8Ohm	109 dB – 115 dB peak
Components	
<ul style="list-style-type: none"> <li>• LF:</li> </ul>	1 x 8'' (203 mm), 1'' voice coil, ( 25 mm)
<ul style="list-style-type: none"> <li>• MF / HF:</li> </ul>	1 x 1'' dome tweeter
Sensitivity @ 8 Ohm	90 dB (1 W @ 1m)
Rated Power @ 8 Ohm	80 W AES, 160 W program, 320 W peak
Transformer taps @ 100v	6,25 W, 12,5 W, 25W, 50 W, 80 W
Coverage	100° H x 90° V
Nominal Impedance	8 Ohm   L100V
Connectors	4 x barrier terminal blocks
Finish	Black and white finish
Material	ABS, painted mesh aluminium grill
Dimensions	241 x 339 x 195 (mm) (H x W x D)
Weight	5 Kg
Fittings	1 x M4 safety, 2 x M4 wall bracket
Accessories	Wall bracket included
Other info	IP66 rating when used with accessory terminal cover

### Accessories

Plastic cover with gland connector and euroblock input connector



Accessories for the wall and safety cable

