Ultra-compact, passive column speaker with $12 \times 3^{\circ}$ (0.75" voice coil) neodymium transducers. $15^{\circ} + -5^{\circ}$ vertical coverage. 121dB SPL. Suitable for outdoors.



General description & specifications

The lonic-100/OD is a passive column speaker part of the lonic series. The lonic columns are compact, modular and powerful and the complete series includes two columns & two subwoofers.

The lonic-100/OD uses 12 x 3" (0.75" voice coil) neodymium transducers offering a coverage of 15° +/-5° V x 100° H and 121dB SPL.

The lonic-100/OD is the ideal column speaker for outdoor installations. The cabinets receive the following treatment so that they can be installed in outside locations: micro perforated

aluminium grill with special polyester protection against water, tropicalized speaker treatment with special latex covering and double cabinet sealing.

Weight has been left as low as possible providing easy set ups in fixed installation as well as easy transport for portable applications.

The Ionic-100/OD is powered from the subwoofer units which include a Digital Signal Processor offering different presets to cover a wide range of sound applications.

Technical Data

Components	12 x 3" speaker with 0.75" voice coil	
Frequency range	150 Hz - 20 KHz (-10dB)	
Frequency response	180 Hz - 18 KHz (± 3dB)	
Sensitivity	96 dB (1W@1m)	
Max SPL	121 dB / 127 dB peak	
Coverage	15° ± 5° V x 100° H	
Power	300 W AES (600 W program, 1200 W peak)	
Nominal Impedance	8Ω	
Connectors	2 x NEUTRIK Speakon NL4	
Finish	Epoxy paint / bespoke pattern	
Material	1.5 mm stainless steel	
Dimensions	1000 x 89 x 117 mm (H x W x D)	
Weight	13 Kg (29 lbs)	

. . .



RAL colours and water-vinyl customization

Available in RAL colours by request. In addition, more customization options for the Ionic 100/OD and Ionic 50/OD cabinets are available. These are some patterns and designs in water-vinyl:


.



Dimensional Drawing



. . . .



.

Accessories

	SV-22	Piece to connect 2 columns together – Straight
	SV-23	Piece to connect columns to wall or truss
	SV-POLE	35mm inclinable Pole adaptor
	SV-12S	Sub adaptor for satellite, combine columns with sub
	SV-2I	Column cabinets connection – inclinable
Ń	WB-120	Wall bracket for column installation – inclinable
	FC-IONIC	Flight case for 2 ionic-100/OD plus accessories

.